Cette page n'est pas encore traduite entièrement. Merci de terminer la traduction
(supprimez ce paragraphe une fois la traduction terminée)

3. Créer le dépôt

Une fois que le site de synchronisation a été configuré, il y a trois approches pour créer et configurer le dépôt qui opérera sur ce site.

- Cela peut être fait «manuellement» comme décrit dans la première méthode ci-dessous.

69/5000 Cette méthode convient si vous ne créez qu'une poignée de magasins.

- If you are creating a larger number of stores, then it is more appropriate to use one or both of the two footrunner code methods. As of 2019-10-24 there are two pieces of footrunner code that can expedite this process - see Creating data files for multiple new remote sites. They can ***not*** be used together for the same store, but it may be appropriate to use store_create_from_name for creation of one store, and then use sync_clone_sync_site to create subsequent stores.

3.01. Manually create store

1. On mSupply desktop go to **Special > Stores > New Store**



2. Enter the Store Code and the Store Name



- The Store Code can not include spaces
- The Store Name needs to be something that users will recognise.
  `Mobile Store 1` is not likely to be a good name to use.

3. Configure items visibility for the store
4. Configure synchronisation settings
5. Configure store visibility to other stores

3.02. Create store from existing customer name using store_create_from_name

Use the footrunner code store_create_from_name. This method is only useful if you already have a customer and you want to convert it to a store.

1. Run `store_create_from_name` to clone the original store. You will need to provide:
    1. Name **ID** (not name **Code**) to create the store for (must not be blank or already a store)
    2. Store mode for new store (one of `store`, `dispensary` or `report`). Almost always, this should be `store`
    3. Sync ID for site on which the new store will be Active (optional; if left blank, will default to the current site ID)
2. Configure items visibility for the store
3. Configure synchronisation settings
4. Configure store visibility to other stores

3.03. Create store by cloning another sync store using sync_clone_sync_site

Use the footrunner code sync_clone_sync_site. Under this method:

1. Manually create and appropriately configure a single store.
2. Make ***sure*** the relevant sync sites have been created (above) and then, for **EACH** store:
3. Run `sync_clone_sync_site` to clone the original store. You will need to provide:
    1. Sync ID for source sync site
    2. Sync ID for clone sync site
    3. sync version (v1 for desktop, v3 for mobile)
    4. Decision on whether the cloned store will have 'group' store visibility (visible to all other stores with the same supplying store) or not
    5. Decision on whether to also clone locations, transactions, stock, requisitions. (almost always **NO**!)
    6. new **store** code *and* name for each cloned store
    7. new **user** name *and* password for the each cloned store's default user
4. If there are actually existing customers for each of these stores, you will need to merge the existing customer name with the new store
5. The store will have the same item visibility configuration as the store that has been cloned. Review, and if necessary, Configure items visibility for the store
6. The store will have the correct 'basic' sync settings. Review, and if necessary, Configure synchronisation settings
7. The store will have the correct 'basic' store visiblity settings, including, if you have selected it, 'group' store visibility. Review, and if necessary, Configure store visibility to other stores

From:
https://wiki.msupply.foundation/ - **mSupply Foundation Documentation**

Permanent link:
https://wiki.msupply.foundation/fr:mobile:setup:server_side:3?rev=1581031057

Last update: **2020/02/06 23:17**